



neat.board 50

# Flow with the moment.

Designed for the flexible future of work, Neat Board 50 swiftly adapts to you whenever, wherever and in whatever way you need to meet or express your ideas. This simple and elegant all-in-one device has a 50-inch touchscreen that empowers you to move, interact, create and collaborate efficiently, all within easy reach. Everything feels just right, giving you more space to think and be productive. More freedom. More choice. It's that simple.

neat.



## Endless possibilities.

Neat Board 50's rich and immersive collaborative canvas lets you run Microsoft Teams or Zoom Rooms or dive into your favorite apps like Browser, Miro, and more for super productive, next-level teamwork. Meanwhile, Neat Active Marker gives you the perfect amount of friction and immediate response to write, markup or sketch as you naturally would, helping infuse more personality into your creative workshops or presentations.

[www.neat.no](http://www.neat.no)

## Deeper engagement.

A custom-built 50-megapixel camera with 113 degrees horizontal field of view and lightning-fast image processing can capture the entire room. Together with our industry-defining auto-framing, Neat Symmetry, it presents everyone equally up close for more natural, equitable and inclusive meetings. In addition, powerful audio processing minimizes disruptive noises, so everyone's always heard, even in lively surroundings.

## Just works.

Neat Board 50 automatically springs to life when it senses your presence, enabling you to move it from space to space and be back up and running fast. With just one tap, you can wirelessly share your screen, start a meeting or begin whiteboarding.

## Room for more.

Whether you're meeting or collaborating one-on-one, in small groups or hosting large gatherings, Neat Board 50 gives you considerable flexibility. It has an HDMI output for a dual-screen setup with an additional display or projector. Alternatively, you can combine two Neat Board 50s to power an extra screen or have your own device run the show through a single USB-C and touchback.

## Adaptable setup.

Neat Board 50 ships with a minimalist table stand that's quick and easy to set up. For greater accessibility, an adaptive stand and wall mount allow anyone to adjust the screen up or down for optimal use and viewing. A wall mount with VESA compatibility is also available for tight-to-the-wall, smarter room integrations.



A black and white photograph of the Neat Board 50, a large conference room display. The image is dark, with the product's features highlighted by white text and icons. The features are arranged in a grid-like pattern over the image. The top row features '50"', '113° FOV', and '50 MP'. The middle row features '4x', '5 mic array', and 'Low distortion speakers'. The bottom row features 'Neat Active Marker', 'WiFi', and 'Air quality sensors'. A dark grey rounded rectangle at the bottom contains the text 'For more information, visit neat.no/board-50'.

# 50"

4K multi-touch LCD screen

# 113° FOV

Wide-angle camera

# 50 MP

Capture resolution

# 4x

Digital zoom



5 mic array



Low distortion speakers



Neat Active Marker



WiFi



Air quality sensors

For more information, visit [neat.no/board-50](https://neat.no/board-50)

## General

50-inch capacitive multi-touch LCD screen  
Ultra HD 4K (3840 × 2160 screen resolution)  
16:9 aspect ratio  
Anti-glare and anti-fingerprint coating  
Glass surface hardness 7H  
USB-C 90W power delivery  
Support for 2nd display  
Camera LED  
System LED  
Ambient light sensor  
Sensors for temperature, humidity and air quality (\*)  
Neat Active Marker  
Table stand

## Video

4x digital zoom (optional 8x digital zoom)  
Fixed lens, infinite focus  
F-value: 2.8  
50 MP capture resolution  
113 degrees horizontal field of view  
Automatic people framing  
Hardware-accelerated video encoding and decoding  
Distortion correction  
Noise reduction  
Chromatic aberration correction  
Automatic white balance and color correction

## Audio

Speaker box for maximum tonal range with minimal distortion  
Opposing drivers for vibration cancellation  
Dedicated wide-angle ultrasonic tweeter  
3 sensor microphones  
5 beamforming microphones angled in an end-fire array  
Hardware-accelerated audio processing (NAP)  
Echo cancellation  
Noise suppression  
Automatic gain control  
Dereverberation

## Electrical and environmental requirements

100-240V ~ 50/60Hz 3.5A  
Ambient operating temperature: 32° to 95° F (0° - 35° C)  
Storage temperature: -4° to 140° F (-20° to 60° C)  
Relative humidity: 10% to 90%  
Built-in power supply

## Size and weight

With table stand  
Width: 44.8 inches (1138 mm)  
Height: 29.3 inches (745 mm)  
Depth: 10.3 inches (261 mm)  
Weight: 52 pounds (23.5 kg)