neat.center

Don't miss a thing.

Neat Center is a companion device that extends the capabilities of Neat devices and Neat Symmetry, enabling remote meeting attendees to enjoy enhanced context and engagement for a more inclusive hybrid meeting experience. It lets them follow the conversation more closely by clearly hearing and seeing their in-office teammates or others, even when those in the room are far away from the main device or facing inward, discussing something among themselves.





Broader vision.

Broaden remote attendees' view with three additional cameras, giving them a 360° visual meeting experience when those in the room are talking among themselves and facing away from the primary video device.

Flexible placement.

Place Neat Center on a table, mount it or hang it from above, whatever suits your meeting room best. Neat Center's 360-degree audiovisual technology will dynamically calibrate the surroundings and scan for people in the room, providing those on the far end with an optimal sound and viewing experience.

Clearer sound.

Allow remote attendees to hear the conversation more clearly with an omnidirectional 16x mic array for optimal audio pickup throughout the room.


Simple setup.

Keep setup simple with just one plug-in network and power cable, enabling Neat Center to work with your Neat Bar or Neat Board to extend remote attendees' audio-visual experience to the center of the room.





neat.



Neat Center

General

3 cameras 360-degree view 16 microphones LED ring status indicator Security lock slot (Kensington compatible) Orientation sensor (accelerometer) Flexible mounting Tripod mount compatible (1/4-20 UNC threads)

Video

Camera: 3 × 8 MP, f/2.4 aperture, 162° horizontal field of view Adaptive digital zoom (up to 4x) Dept of field: 0.8 feet (25 cm) to infinity 9.8 feet (3 meters) pickup range for optimal image quality Automatic people framing Hardware-accelerated video encoding Distortion correction Noise reduction Automatic white balance and color correction People video resolution: Up to 1080p / 30

Audio

16 microphones in a beamforming array Pickup range: 9.8 feet (3 meters) radius *** Hardware-accelerated audio processing Echo cancellation Noise suppression Automatic gain control Dereverberation

Electrical and environmental requirements

Ambient operating temperature: 32° to 95° F (0° - 35° C) Storage temperature: -4° to 140° F (-20° to 60° C) Relative humidity: 10% to 90%

Power consumption Idle: 2W In a call: 6-9 W

Size and weight

Height: 11.7 inches (297 mm) Width: 3.3 inches (84 mm) Depth: 3.3 inches (84 mm) Weight: 3.24 pounds (1.47 kg)